ATKOL
WWW.ATKOLOIL.COM

HIGH PERFORMANCE
LUBRICANTS
FOR A STRONGER
TOMORROW

PRODUCT DATA SHEET

ATKOL HP 68 Hydraulic Oil

ATKOL HP 68 is a high-quality hydraulic oil with an ISO VG 68 viscosity grade, designed to lubricate and protect a wide range of hydraulic systems and industrial equipment. It is an ashless and zinc-free (Zn-Free) product, making it suitable for systems containing soft, non-ferrous alloys and components, such as copper and bronze.

Formulated using premium base oils and specialized additives, this oil provides effective lubrication while helping to protect system components against wear, oxidation, rust, and corrosion.

**Advantages:**

-Extending the system's lifespan
-Good air release properties
-Excellent oxidation and thermal stability
-Excellent water separability
-Excellent protection of parts against rust and corrosion.
-Excellent oxidative and thermal stability
-Excellent resistance to rust and corrosion.

**Technical Specification of HP68 Hydraulic Atkol Oil**

| ISO | Range | |
|---|---|---|
| K1inematic viscosity @40°c | 68 | D-445 |
| K1inematic viscosity @100°c | 8.5 | D-445 |
| Viscosity Index | 95 | D-2270 |
| Flash point °c | 218 | D-92 |
| Pour point °c | -24 | D-97 |
| Density @15°c, kg/m³ | 0.875 | D-1298 |