ATKOL
WWW.ATKOLOIL.COM

HIGH PERFORMANCE
LUBRICANTS
FOR A STRONGER
TOMORROW

PRODUCT DATA SHEET

ATKOL 100 Plus Compressor Oil

ATKOL 100 Plus compressor oil, featuring an ISO VG 100 grade and formulated with Group II and III base oils, is designed for the lubrication and protection of industrial air compressors. Compared to conventional VDL compressor oils, this product offers superior oxidative and thermal stability, along with more effective control over sludge and deposit formation.

These characteristics help maintain stable oil performance during continuous operation, reduce component wear, and extend the service life of both the oil and the equipment.

Advantages:
-Formulated using Group II and III base oils.
-High oxidation stability and favorable RBOT
-Good resistance to heat and oil degradation.
--Control of sludge and deposit formation
-Protection of bearings and rotating parts
-Suitable for turbines and industrial lubrication systems.
-Stable performance during long-term operation

Technical Specification of **Turbine 100 PLUS Atkol** Oil

Property	100	Test method (ASTM)
Kinematic viscosity @40°c	100	D-445
Viscosity Index	135	D-2270
Flash point °c	215	D-92
Pour point °c	-27	D-97
Density @ 15°c, kg/m³	850	D-1298